

ELASTIGUM PAINT

Fixative primer for painting of bituminous powdered and sandblasted membranes

Description: Water-based fixative product, formulated with bitumen, selected resins and special additives.

Advantages:

- Excellent adhesion on talcquered and sandblasted bitumen-polymer membranes.
- Protects the polymer bitumen membranes from degradation caused by UV rays.
- Reduces the degradation of paints applied on insufficiently aged membranes.
- Odourless and not flammable.
- Non-toxic, solvent free.

Application fields:

- Primer coat to be applied on bitumen-polymer membranes with talc and sandblasted finish, both new and aged. The laying of Elastigum Paint fixes the excess surface talc and blocks the detaching action of the water-soluble powder, making it possible to paint the membranes without long waits.
- Especially suitable for waterproofing works in residential areas, where the use of solvent based products is not recommended.

Surface preparation:

- Make sure that the surface is free from detached parts, loose debris or non-adherent parts, coatings, rust, powder, disarming oils and carefully clean the surfaces, that must be sound and dry. Do not apply if bad weather is forecast, which could negatively influence the correct product drying.

Application:

- Apply by brush, roller or airless spray.
- Slightly mix before use.
- To clean the tools use water or common synthetic diluents.

Consumption: - The consumption is strongly influenced by the porosity and consequently by the absorption of the surface. The average consumption is of 150÷250 g/m².

Warning:

- It is not recommended to apply at extreme temperatures, both of the environment and of the surface, as the drying process would be excessively accelerated with negative consequences on the cohesion and adhesion of the paint to the substrate.
- Do not apply on wet or damp surfaces.
- Apply only on surfaces with regular water flow.
- Do not use it to seal surfaces or containers suitable for edible liquids, drinking water or others, that is in contact with solvents or mineral oils.
- The product must be applied or stocked at a temperature above +5° C. Once frozen, the product is not reusable anymore.
- For further information please ask for safety datasheet.
- Read the information reported at the end of this data sheet.

Packaging: Metal or plastic pails of 1, 5, 10, 20, 25 kg.
Metal drums of 200 kg.
IBCs of 1.000 kg.

ELASTIGUM PAINT

Fixative primer for painting of bituminous powdered and sandblasted membranes

Technical data:

MAIN CHARACTERISTICS		
Aspect		Liquid
Colour		Brown (black, once dried)
Shelf life in closed original container		12 months
Solid content (m/m drying at 130 °C)	EN ISO 3251	(38÷42)%
Brookfield viscosity (at 20°C, Impeller n.2; 20 rpm)	EN ISO 3219	(400±80)cP
Density (at 20°C)	EN ISO 2811-1	(1,10÷1,18)kg/L
pH (at 20° C)		7,0÷9,0

* Measures have been recorded with a temperature of 23°C and a moisture of 50%. Declared data can change depending on the thickness of applied product and on the specific conditions of the construction site: temperature, humidity, ventilation, absorption capacity of surfaces.

The advice and technical information here provided represent HA ITALIA best knowledge of product properties and use. Considering the different uses of the products and other factors which do not depend on us (different materials, working conditions, non-compliance with instructions), we cannot be held responsible for the results obtained. Before using the product, anyone who intends to use it must determine its suitability for the intended use and has all liability that may arise from its use. **HA Italia disclaims any liability arising from non-compliance with the instructions given in this technical data sheet and with the guidelines specified in the safety data sheets.**

Datasheet no.: 20004534-REV01 dtd 01.01.2023



HA ITALIA S.p.A.
SPECIAL PRODUCTS DIVISION
 Viale della Scienza 78 -80 - 36100 Vicenza - Italy
 Plant Via Vicenza 72 - 36015 Schio (VI)
 P.I. e C.F. IT00169590247 - Ph +39 0445 678000
 info@ha-italia.com - www.ha-italia.com -  ha italia s.p.a -  ha italia s.p.a

