

PRIMER BIT 50-50 WET SPRAY

Multi-purpose bituminous primer spray

Description: Very fast drying primer, formulated with bitumen and pure organic solvents, in a spray can.

Advantages:

- Long-lasting protective action.
- Blocks the effects of dust and minimises porosity in concrete.
- Rapid drying of film, no stickiness.
- Excellent adhesion on cement surfaces even if slightly damp.
- No superficial oily substances.
- Resistant to weathering and salt corrosion.
- Increases the adhesion of anticorrosive tapes at low temperatures.
- Ready for use.
- Easy to apply.

Applications:

- Suitable for any type of surface, including metal, concrete, plastic and wood.
- Adheres to any shape.
- Priming coat on concrete structures such as viaducts, bridges, foundation walls, roofing of civil and industrial buildings.
- Surfaces of bridges, roofs, pillars, steel structures, tanks, agricultural machinery chassis, car bodies, etc.
- Preparation of surfaces and pipes before laying anticorrosive tapes, sleeves, slabs, etc.
- Useful during the installation of fireplaces, solar panels, satellite dishes and antennas.
- Protection of port and railway materials.

Surface preparation: Make sure that the surface is free from detached parts, loose debris or non-adherent parts, coatings, rust, powder, or release oils. Carefully clean the surfaces, which must be solid, even, and dry and in the case of concrete surfaces must not have been previously treated with evaporation retardant products. Avoid application if bad weather is forecast, as it could negatively affect the proper drying of the product.

- Apply at temperatures between 0°C and +35°C; avoid extremely hot or cold conditions during application and drying of the film.

Application:

- Shake the can well until you can hear the steel ball moving inside.
- Spray intermittently to maintain a uniform jet.
- Drying time depends on the thickness of the layer, the type of surface and ambient conditions.

Once the application is finished, turn over the can and spray for 1-2 seconds so that the nozzle remains clean and does not get blocked.

Consumption: -One 500 ml spray can covers an area of about 3-4 m² depending on the desired layer thickness.

PRIMER BIT 50-50 WET SPRAY

Multi-purpose bituminous primer spray

Warnings:

- Do not use indoors or in non-ventilated premises.
- Store in tightly sealed original packaging.
- Do not use to waterproof surfaces or containers intended to contain edible liquids, drinking water or which are in contact with solvents or mineral oils.
- Flammable product.
- Do not expose to direct sunlight, temperatures higher than 30 °C, heat sources, open flames or other sources of ignition.
- Pressurized container: may explode if heated.
- Do not pierce or burn, even after use.
- Comply with the information on the safety data sheet.
- Consult the information at the bottom of this document.

Packaging:

400 or 500 ml spray cans in boxes of 6/12/24 pcs.

Technical data:

MAIN CHARACTERISTICS		
Appearance		Liquid
Colour		Black
Shelf life in closed original packaging		24 months
Drying time		5 - 15 minutes*

* Measurements have been recorded at a temperature of 23 °C and with 50% moisture. Declared data may vary depending on the thickness of the applied product and on the specific conditions of the construction site: temperature, humidity, ventilation, and absorbency of surfaces.

The advice and technical information provided represent HA ITALIA S.p.A.'s best knowledge of product properties and use. Considering the different situations of use of the products and factors beyond our control (media, working conditions, failure to comply with instructions), we cannot be held responsible for the results obtained. Before using the product, anyone who intends to make use of it is required to determine whether it is suitable for the intended use and assumes full liability for whatever may arise from its use.

HA Italia disclaims any and all liability arising from failure to observe the warnings mentioned in this data sheet and failure to comply with the requirements set out in the safety data sheet.

Data sheet no.: 20004126-REV01 dated 01.01.2023