

**Description:** Medium drying anhydrous hydrocarbon-based thinner, to be used in combination with solvent-based sheaths and paints.

**Advantages:**

- Liquid.
- Colourless.
- Allows the creation of the primer starting from the chosen liquid membrane.
- Soluble in the most common organic solvents.

**Applications:**

- Dilution of liquid sheaths.
- Dilution of enamels and synthetic rust inhibitors for brush application.
- Dilution of paints.

**Application:** - For waterproofing porous concrete surfaces, apply a coat of primer before spreading the liquid sheath by diluting the liquid membrane such as Elastiden C or Elastiden Plus 50% with Diluxil.

**Warnings:**

- Flammable product.
- Do not use in non-ventilated premises.
- Do not expose to heat sources, open flames or other sources of ignition.
- Comply with the information on the safety data sheet.
- Consult the information at the bottom of this document.

**Packaging:** 4 kg metal pails.

#### Technical data:

MAIN CHARACTERISTICS		
Appearance		Liquid
Colour		Colourless
Shelf life in closed original packaging		24 months
Closed-cup flash point	ASTM D3828-87	> +21 °C
Density (at 20 °C)	EN ISO 2811-1	(0.86-0.87) kg/L

The advice and technical information provided represent HA ITALIA S.p.A.'s best knowledge of product properties and use. Considering the different situations of use of the products and factors beyond our control (media, working conditions, failure to comply with instructions), we cannot be held responsible for the results obtained. Before using the product, anyone who intends to make use of it is required to determine whether it is suitable for the intended use and assumes full liability for whatever may arise from its use.

**HA Italia disclaims any and all liability arising from failure to observe the warnings mentioned in this data sheet and failure to comply with the requirements set out in the safety data sheet.**

Data sheet no.: 20004807-REV01 dated 01.01.2023