

# ELASTIDEN UP

## Bituminous sealant spray

- Description:** Solvent-based waterproofing sealant/protective coating, formulated with bitumen, selected elastomeric resins and special additives, packaged in a spray can.
- Advantages:**
- Long-lasting protective action.
  - High flexibility.
  - Fast drying.
  - Resistant to weathering and salt corrosion.
  - Seals cracks and stops leaks.
  - Ready for use.
  - Easy to apply.
- Applications:**
- Suitable for any type of surface, including metal, concrete, plastic and wood.
  - Adheres to any shape.
  - Seals leaks in roofs, gutters, roof tiles and terraces, skylights, PVC or metal drain pipes.
  - To coat and protect surfaces of bridges, roofs, pillars, steel structures, tanks, agricultural machinery chassis, car bodies, etc.
  - Seals details during the installation of fireplaces, solar panels, satellite dishes and antennas.
  - Protection of port and railway materials.
- Surface preparation:** Make sure that the surface is free from detached parts, loose debris or non-adherent parts, coatings, rust, powder, or release oils; carefully clean the surfaces, which must be sound and dry.
- Application:**
- Shake the can well until you can hear the steel ball moving inside.
  - Spray intermittently to maintain a uniform jet.
  - Drying time depends on the thickness of the applied layer, the type of surface and ambient conditions.
  - Once the application is finished, turn over the can and spray for 1-2 seconds so that the nozzle remains clean and does not get blocked.
- Consumption:** -One 500 ml Elastiden Up spray can covers an area of about 4 m<sup>2</sup> depending on the desired layer thickness.
- Warnings:**
- Apply at ambient temperatures between +5 °C and +30 °C.
  - Do not use indoors or in non-ventilated premises.
  - Store in tightly sealed original packaging.
  - Flammable product.
  - Do not expose to direct sunlight, temperatures higher than 30 °C, heat sources, open flames or other sources of ignition.
  - Pressurized container: may explode if heated.
  - Do not pierce or burn, even after use.
  - Comply with the information on the safety data sheet.
  - Consult the information at the bottom of this document.
- Packaging:** 500 ml spray cans in boxes of 6/12/24 pcs.

# ELASTIDEN UP

## Bituminous sealant spray

### Technical data:

| MAIN CHARACTERISTICS                    |  |                      |
|---|--|----------------------|
| Appearance                              |  | Dense paste in spray |
| Colour                                  |  | Black                |
| Shelf life in closed original packaging |  | 24 months            |
| Drying time                             |  | 60-240 minutes*      |

\* Measurements have been recorded at a temperature of 23 °C and with 50% moisture. Declared data may vary depending on the thickness of the applied product and on the specific conditions of the construction site: temperature, humidity, ventilation, and absorptency of surfaces.

The advice and technical information provided represent HA ITALIA S.p.A.'s best knowledge of product properties and use. Considering the different situations of use of the products and factors beyond our control (media, working conditions, failure to comply with instructions), we cannot be held responsible for the results obtained. Before using the product, anyone who intends to make use of it is required to determine whether it is suitable for the intended use and assumes full liability for whatever may arise from its use.

**HA Italia disclaims any and all liability arising from failure to observe the warnings mentioned in this data sheet and failure to comply with the requirements set out in the safety data sheet.**

Data sheet no.: REV01 dated 01.01.2023

|   |  |  |
|---|--|--|
|  | <p><b>HA ITALIA S.p.A.</b><br/><b>DIVISIONE PRODOTTI SPECIALI</b></p> <p>Viale della Scienza 78 -80 - 36100 Vicenza - Italy<br/>Stabilimento Via Vicenza 72 - 36015 Schio (VI)<br/>P.I. e C.F. IT00169590247 - Ph +39 0445 678000<br/>info@ha-italia.com - www.ha-italia.com  ha italia s.p.a -  ha italia s.p.a</p> |  <p>MANAGEMENT SYSTEM CERTIFICATION<br/><b>DNV</b><br/>ISO 9001 - ISO 14001<br/>ISO 45001 - ISO 50001</p> |
|---|--|--|